

Future Gallium Nitride Sputter Deposition Development at PVD Products

September 2020

At PVD Products we are continuing to advance our GaN sputtering technology. During our recent webinar, sputtering from a liquid Gallium magnetron was described. PVD Products has recently designed its third-generation *solid* Gallium magnetron (photo). This gun builds on our experience with Gallium magnetrons as well as our standard magnetrons. We are engaging with our partner at Linkoping University to apply this gun for epitaxial GaN film growth. Here are main features of this gun:

- 3" outer diameter, allowing deposition onto larger area substrates (for scaling)
- UHV-compatible
- Gallium is loaded into the cup and solidified (near room temperature)
- Gun features cooling with lowtemperature fluids in specialized chillers, for operation at -10 to -20°C
- The Gallium can thus be kept solid even under plasma bombardment during the sputtering process
- The circumferential magnets and the center pole-piece can be changed, to allow experimentation with different magnetic field configurations



• The bottom flange is a Conflat at ground potential, allowing the head to be mounted on a re-entrant nipple or Z-stage, for setting the desired target-to-substrate distance.

Our work with the Linkoping University group will determine operating parameters and capabilities of this gun for reactive deposition of GaN films and nano-structures. We will provide updates on the results as they become available.

PVD Products, Inc. ▼ 35 Upton Drive, Suite 200 ▼ Wilmington, MA 01887-1018

Phone: 978.694.9455 ▼ www.pvdproducts.com ▼ Fax: 978.694.9477